



GARDEN AND POETRY
2025

inverlight



FORGED BY NATURE

Inspiration derived from nature, often referred to as 'biophilic design,' is a creative approach that seeks to incorporate elements and principles of nature into design and creation processes.

Light in nature is a fundamental element that plays a crucial role in natural ecosystems and significantly influences life on Earth.

Its importance underlines the need to protect and conserve natural ecosystems and to consider artificial lighting and its potential interference with the natural environment.

Good artificial lighting should be designed to respect the natural surroundings.

This means that it should minimise light pollution so as not to disturb nocturnal wildlife or alter natural ecosystems.

The planning and implementation of environmentally sensitive lighting solutions are essential to achieve these goals.

At Inverlight these principles are held in high regard.





INOX



BROWNTech



NATURALBLACK

THE COLORS

The material is one but the colors are three: **inox**, **browntech** and **naturalblack**.

The **inox** color is the classic tone of this material.

Browntech is a brown color tending to opaque brown with slight irregular shades.

It is a color obtained after years of research and experimentation through a process that allows us to obtain a transformation of the stainless steel surface without adding other materials such as paints or various protective products. This allows to obtain a very natural effect, with the presence of small differences in tones and shades, as it happens with materials such as wood, stone or granite.

Naturalblack is obtained with a special very opaque painting on several layers that combines exceptional durability with an aesthetic effect that mix well with the environment and the landscape.

High quality solutions
to lighten the dark.
Exclusively in stainless steel.



OTELLO
6



AMANITA
12



NORMA
76



MANTRA
80




TOSCA
124



CHIODINO 4
132



CASTA DIVA
190



BALOSS
226



RASCASSE
262



YUUKI 6 / 13
268



SOFFIONE MINI P1 / P3
22



SOFFIONE P1 / P3
26



TRAVIATA
36



CARNOUSTIE
42



CARNOUSTIE GIRAFFE
68



SURSUM CORDA
72



SPIRIT OF FLORENCE
104



SPIRIT OF PARIS
108



MADAMA BUTTERFLY
112



FAUST
116



AD HOC
118



NABUCCO
120



CHIODINO 7
134



CHIODINO 13
140




ALTER EGO
150



ACORUS
154



CARMEN
162



MEDEA
176



CHAPPARAL
228



AD LUNAM
232



NESSUN DORMA
236



MIMI
248



BAMBOO
254



BACKSPIN PLUS / XL
256



SAM
272



MARELL 6 / 13 / 22
274



FOLLOW ME
282



MR HELP
284



ENERGY GHOST
286



Otello 5





LED 1.5W / 150 lm / 24V / H 600 mm

OTP5BH1 ■ ■ ■

LED 1.5W / 150 lm / 24V / H 1100 mm

OTP5BH2 ■ ■ ■

LED 1.5W / 150 lm / 24V / H 1600 mm

OTP5BH3 ■ ■ ■

LED 1.5W / 150 lm / 24V / H 2000 mm

OTP5BH4 ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech

Drivers 24V p. 286

Otello 5


CE LED IP65 IK07 24V

Stainless steel AISI 316L

Spike to be buried

Equipped with 3 mt cable

Driver 24V not included





LED 4W / 400 lm / 24V / H 600 mm

OTP7BH1 ■ ■ ■

LED 4W / 400 lm / 24V / H 1100 mm

OTP7BH2 ■ ■ ■

LED 4W / 400 lm / 24V / H 1600 mm

OTP7BH3 ■ ■ ■

LED 4W / 400 lm / 24V / H 2000 mm

OTP7BH4 ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech

Drivers 24V p. 286

Otello 7


CE LED IP65 IK07 24V

Stainless steel AISI 316L

Spike to be buried

Equipped with 3 mt cable

Driver 24V not included










LED 1,5W / 150lm / 24V / H 700 mm

AM6P1H1    

LED 1,5W / 150lm / 24V / H 1000 mm

AM6P1H2    

LED color	Finishing
1 2200 K	IN 
2 2700 K	BT 
3 3000 K	NB 

Drivers 24V p. 286

Amanita 6


CE  IP65 IK08 24V

Stainless steel AISI 316L

Spike to be buried

Supplied with 3 mt cable

Driver 24V not included





LED 4W / 400lm / 24V / H 700 mm

AM9P1H1 ■ ■ ■ ■

LED 4W / 400lm / 24V / H 1000 mm

AM9P1H2 ■ ■ ■ ■

LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Amanita 9


CE LED IP65 IK08 24V

Stainless steel AISI 316L

Spike to be buried

Supplied with 3 mt cable

Driver 24V not included





CABLE VERSION

LED 4W / 400lm / 220-240V / H 1500 mm

AM17P1H1    

RECHARGEABLE

LED 4W / 400lm / H 1500 mm

AM17P2H1    

LED 4W / 400lm / H 600 mm

AM17P2H2    

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Amanita 17

CE  IP65 IK08 24V

Stainless steel AISI 316L

Cable version: supplied with 3 mt cable and driver

Rechargeable version: rechargeable with 7 hours autonomy





LED 7W / 700lm / 24V / H 700 mm

AM20F1H1 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 1000 mm

AM20F1H2 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 1500 mm

AM20F1H3 ■ ■ ■

LED 7W / 700lm / 220-240V / H 700 mm

AM20F2H1 ■ ■ ■ ■

LED 7W / 700lm / 220-240V / H 1000 mm

AM20F2H2 ■ ■ ■ ■

LED 7W / 700lm / 220-240V / H 1500 mm

AM20F2H3 ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech

NB Naturalblack

Drivers 24V p. 286


Amanita 20

CE **LED** IP65 IK08 24V / 220-240V

Stainless steel AISI 316L

Fixing with housing to be buried

Opal diffuser





LED 0,5W / 50 lm / 24V / H 600 mm

SMP1BH1 ■ ■ ■

LED 0,5W / 50 lm / 24V / H 900 mm

SMP1BH2 ■ ■ ■

LED 0,5W / 50 lm / 24V / H 1200 mm

SMP1BH3 ■ ■ ■

LED 0,5W / 50 lm / 24V / H 1500 mm

SMP1BH4 ■ ■ ■

- LED color

■

 Diffuser's lenght
- A** 2700 k

5 50 mm
- B** 2200 k

8 80 mm
- C** green

D blue

E red

F yellow

- Finishing
- IN**

Inox
- BT**


Browntech

Drivers 24V p. 286

Soffione mini P1

CE LED IP65 IK07 24V

Stainless steel AISI 316L
Fixing into the ground with spike
Diffuser in PMMA L= 50mm and 80mm
LED 2700 k, LED 2200 k, green, blue, red, yellow
Supplied with cable L= 3 mt
Driver 24V not included





LED 0,5W / 50 lm / 24V / H 600 mm

SMP3BH1P ■ ■ ■

LED 0,5W / 50 lm / 24V / H 900 mm

SMP3BH2P ■ ■ ■

LED 0,5W / 50 lm / 24V / H 1200 mm

SMP3BH3P ■ ■ ■

LED 0,5W / 50 lm / 24V / H 1500 mm

SMP3BH4P ■ ■ ■

■ LED color

A 2700 k

B 2200 k

C green

D blue

E red

F yellow

Finishing

IN Inox

BT Browntech

Drivers 24V p. 286

Soffione mini P3

CE LED IP65 IK07 24V

Stainless steel AISI 316L


Fixing into the ground with spike

Diffuser in PMMA diameter 40 mm

LED 2700 k, LED 2200 k, green, blue, red, yellow

Supplied with cable L= 3 mt

Driver 24V not included





Soffione P1





G4 / 1,6W / 200lm / 12V / H 600 mm

SOP1AH1 ■ ■ ■

G4 / 1,6W / 200lm / 12V / H 1100 mm

SOP1AH2 ■ ■ ■

G4 / 1,6W / 200lm / 12V / H 1600 mm

SOP1AH3 ■ ■ ■

G4 / 1,6W / 200lm / 12V / H 2000 mm

SOP1AH4 ■ ■ ■

LED / 1W / 100lm / 24V / H 600 mm

SOP1BH1 ■ ■ ■ ■

LED / 1W / 100lm / 24V / H 1100 mm

SOP1BH2 ■ ■ ■ ■

LED / 1W / 100lm / 24V / H 1600 mm

SOP1BH3 ■ ■ ■ ■

LED / 1W / 100lm / 24V / H 2000 mm

SOP1BH4 ■ ■ ■ ■

LED color	Diffuser's lenght
1 2200 K	10 100 mm
2 2700 K	13 130 mm
	20 200 mm

Finishing
IN Inox
BT Browntech

Drivers 12V and 24V p. 286

Soffione P1

CE G4 IP65 IK07 12V-24V

Stainless steel AISI 316L


Spike to be buried

Hand blown sand blasted glass L= 100, 130 and 200mm

G4 version with LED bulb included and version with LED card integrated

Supplied with 3 mt cable

Driver 12V (G4) or driver 24V (LED) not included





Soffione P3





G4 / 1,6W / 200lm / 12V / H 600 mm

SOP3AH1 ■ ■ ■

G4 / 1,6W / 200lm / 12V / H 1100 mm

SOP3AH2 ■ ■ ■

G4 / 1,6W / 200lm / 12V / H 1600 mm

SOP3AH3 ■ ■ ■

G4 / 1,6W / 200lm / 12V / H 2000 mm

SOP3AH4 ■ ■ ■

LED / 1W / 100lm / 24V / H 600 mm

SOP3FH1 ■ ■ ■

LED / 1W / 100lm / 24V / H 1100 mm

SOP3FH2 ■ ■ ■

LED / 1W / 100lm / 24V / H 1600 mm

SOP3FH3 ■ ■ ■

LED / 1W / 100lm / 24V / H 2000 mm

SOP3FH4 ■ ■ ■

■ Diffuser's finishing	Finishing
T Transparent	IN Inox
S Sand-blasted	BT Browntech

Drivers 12V and 24V p. 286

Soffione P3

CE G4 IP65 IK07 12V-24V

Stainless steel AISI 316L


Spike to be buried

Hand blown sand blasted or transparent glass

G4 version with LED bulb included and version with LED card integrated

Supplied with 3 mt cable

Driver 12V (G4) or driver 24V (LED) not included





G4 / 1,6W / 200lm / 12V / H 600 mm

SOP3BH1 BT ■ ■ ■

G4 / 1,6W / 200lm / 12V / H 1100 mm

SOP3BH2 BT ■ ■ ■

G4 / 1,6W / 200lm / 12V / H 1600 mm

SOP3BH3 BT ■ ■ ■

G4 / 1,6W / 200lm / 12V / H 2000 mm

SOP3BH4 BT ■ ■ ■

LED / 1W / 100lm / 24V / H 600 mm

SOP3GH1 BT ■ ■ ■

LED / 1W / 100lm / 24V / H 1100 mm

SOP3GH2 BT ■ ■ ■

LED / 1W / 100lm / 24V / H 1600 mm

SOP3GH3 BT ■ ■ ■

LED / 1W / 100lm / 24V / H 2000 mm

SOP3GH4 BT ■ ■ ■

Diffuser's finishing

AM Amber

VE Green

FU Smoked

Drivers 12V and 24V p. 286

Soffione P3 colors

CE LED IP65 IK06 12V-24V

Stainless steel AISI 316L


Spike to be buried

Hand blown transparent glass L= 100, 130 and 200mm

G4 version with LED bulb included and version with LED card integrated

Supplied with 3 mt cable

Driver 12V (G4) or driver 24V (LED) not included









LED 4W / 400lm / 24V / H 1000 mm

TR1F2H1

Accessories

ZA010 Housing


LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Traviata

CE LED IP65 IK08 24V

Stainless steel AISI 316L
Fixing into the ground with housing in stainless steel
Mouth-blown transparent glass diffuser





LED 4W / 400lm / 24V
TRW1F1H1    

LED 4W / 400lm / 220-240V
TRW2F1H1    


LED color	Finishing
1 2200 K	IN  Inox
2 2700 K	BT  Browntech
3 3000 K	NB  Naturalblack

Drivers 24V p. 286

Traviata wall

  IP65 IK08 24V / 220-240V

Stainless steel AISI 316L
Fixing to the wall
Mouth-blown transparent glass diffuser





Carnoustie maxi





LED 5.5W / 550lm / 24V / H 600 mm

CNX1P1H1    

LED 5.5W / 550lm / 24V / H 1000 mm

CNX1P1H2    

LED 5.5W / 550lm / 24V / H 1300 mm

CNX1P1H3    

Accessories

ZA005 Housing

ZA006 Spike


LED color	Finishing
1 2200 K	IN 
2 2700 K	BT 
3 3000 K	NB 

Drivers 24V p. 286

Carnoustie maxi

CE  IP65 IK08 24V

Stainless steel AISI 316L
Fixing to the ground with housing in stainless steel or spike
Supplied with 3 mt cable
Opal diffuser
Driver 24V not included





LED 5.5W / 550lm / 24V
CNXW1P1    


LED color	Finishing
1 2200 K	IN 
2 2700 K	BT 
3 3000 K	NB 

Drivers 24V p. 286

Carnoustie maxi wall

  IP65 IK08 24V

Stainless steel AISI 316L
Fixing to the wall
Opal diffuser
Driver 24V not included









4W / 400lm / 24V / H 600 mm

CN1P1H1    

4W / 400lm / 24V / H 1000 mm

CN1P1H2    

4W / 400lm / 24V / H 1300 mm

CN1P1H3    

Accessories

ZA005 Housing

ZA006 Spike

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Drivers 24V p. 286

Carnoustie

CE  IP65 IK08 24V


Stainless steel AISI 316L

Fixing to the ground with spike or housing

Supplied with 3 mt cable

Opal diffuser

Driver 24V not included





4W / 400lm / 24V

CNA1P1H1

Accessories

ZA005 Housing

ZA007 Spike

LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	

Drivers 24V p. 286

Carnoustie arco

CE LED IP65 IK08 24V


Stainless steel AISI 316L

Fixing to the ground with spike or housing

Supplied with 3 mt cable

Opal diffuser

Driver 24V not included





4W / 400lm / 24V / H 300 mm

CNC1P1H1 ■ ■ ■ ■

4W / 400lm / 24V / H 400 mm

CNC1P1H2 ■ ■ ■ ■

4W / 400lm / 24V / H 500 mm

CNC1P1H3 ■ ■ ■ ■

4W / 400lm / 24V / H 700 mm

CNC1P1H4 ■ ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech


NB Naturalblack

Drivers 24V p. 286

Carnoustie ceiling

CE LED IP65 IK08 24V

- Stainless steel AISI 316L
- Ceiling fixing
- Opal diffuser
- Driver 24V not included





Carnoustie wall





4W / 400lm / 24V / H 170 mm

CNW1P1 ■ ■ ■ ■

4W / 400lm / 24V / H 300 mm

CNW2P1 ■ ■ ■ ■

4W / 400lm / 24V / H 600 mm

CNW3P1 ■ ■ ■ ■


LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Carnoustie wall

CE LED IP65 IK08 24V

Stainless steel AISI 316L
Fixing to the wall
Opal diffuser
Driver 24V not included





Carnoustie mini



LED 1,5W / 150lm / 24V / H 400 mm

CNMP1H1    

LED 1,5W / 150lm / 24V / H 600 mm

CNMP1H2    

LED 1,5W / 150lm / 24V / H 800 mm

CNMP1H3    

Accessories

ZA005 Housing

ZA006 Spike


LED color		Finishing	
1	2200 K	IN	Inox
2	2700 K	BT	Browntech
3	3000 K	NB	Naturalblack

Drivers 24V p. 286

Carnoustie mini

CE LED IP65 IK07 24V

- Stainless steel AISI 316L
- Fixing to the ground with spike or housing
- Supplied with 3 mt cable
- Opal diffuser
- Driver 24V not included





The image shows two identical outdoor lamps with dark, curved poles and conical shades. They are positioned in a garden with green foliage and grass. The lamp on the left is in the foreground, and the one on the right is slightly further back. The background is a dense thicket of green bushes.

Carnoustie mini arco



LED 1,5W / 150lm / 24V
CNMAP1H1

Accessories

- ZA005 Housing
- ZA007 Spike


LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Carnoustie mini arco

CE LED IP65 IK07 24V

- Stainless steel AISI 316L
- Fixing to the ground with spike or housing
- Supplied with 3 mt cable
- Opal diffuser
- Driver 24V not included







Carnoustie giraffe



LED 4W / 400lm / 24V / H 3000 mm

CNG1P1H1 ■ ■ ■ ■

LED 6W / 600lm / 24V / H 3000 mm

CNG2P1H1 ■ ■ ■ ■

Accessories

ZA010 Housing


LED color	LED lens	Finishing
2 2700 K	X 18°	IN Inox
3 3000 K	Y 25°	BT Browntech
	Z 38°	

Drivers 24V p. 286

Carnoustie giraffe

CE LED IP65 IK08 24V

Stainless steel AISI 316L
Fixing into the ground with housing in stainless steel
Supplied with cable L= 3 mt
Opal diffuser
Driver 24V not included





Sursum corda





LED 14W / 1400lm / 220-240V / H 2000 mm

SCP1AF1H1 ■ ■ ■ ■

LED 14W / 1400lm / 220-240V / H 2500 mm

SCP1AF1H2 ■ ■ ■ ■

Accessories

ZA011 Kit to be buried for fixing in concrete

■ LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286


Sursum corda

CE LED IP65 IK08 220-240V

Stainless steel AISI 316L

Opal polycarbonate diffuser

Ground fixing with plugs or optional kit





Norma





LED 2W / 200lm / 24V / H 400 mm

NOP1H1

LED 2W / 200lm / 24V / H 600 mm

NOP1H2

LED 2W / 200lm / 24V / H 800 mm

NOP1H3


 LED color	Finishing
2 2700 K	IN Inox
3 3000 K	BT Browntech
	NB Naturalblack

Drivers 24V p. 286

Norma

CE LED IP65 IK07 max 24V

Stainless steel AISI 316L
Fixing to the ground with spike
Supplied with 3 mt cable
Opal diffuser
Driver 24V not included





Mantra mini





LED 3W / 360lm / 24V / H 600 mm

MMF1H1

LED 3W / 360lm / 24V / H 900 mm

MMF1H2

Accessories

ZA005 Housing

ZA006 Spike

LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Mantra mini

CE LED IP65 IK08 24V

Stainless steel AISI 316L


Indirect light

Fixing to the ground with housing in stainless steel or spike

Opal diffuser

Supplied with 3 mt cable

Driver 24V not included





LED 3W / 360lm / 24V / H 270 mm


MMW1P1    

LED 3W / 360lm / 24V / H 400 mm

MMW2P1    

LED 3W / 360lm / 24V / H 700 mm

MMW3P1    


LED color	Finishing
1 2200 K	IN  Inox
2 2700 K	BT  Browntech
3 3000 K	NB  Naturalblack

Drivers 24V p. 286

Mantra mini wall

  IP65 IK08 24V

- Stainless steel AISI 316L
- Indirect light
- Fixing to the wall
- Opal diffuser
- Driver 24V not included





LED 3W / 400lm / 24V / H 300 mm

MMC1P1H1 ■ ■ ■ ■

LED 3W / 400lm / 24V / H 400 mm

MMC1P1H2 ■ ■ ■ ■

LED 3W / 400lm / 24V / H 500 mm

MMC1P1H3 ■ ■ ■ ■

LED 3W / 400lm / 24V / H 700 mm

MMC1P1H4 ■ ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech


NB Naturalblack

Drivers 24V p. 286

Mantra mini ceiling

CE LED IP65 IK08 24V

- Stainless steel AISI 316L
- Indirect light
- Fixing to the ceiling
- Opal diffuser
- Driver 24V not included





LED 3W / 360lm / 24V / H 200 mm

MMT1P1    

LED color	Finishing
1 2200 K	IN 
2 2700 K	BT 
3 3000 K	NB 

Drivers 24V p. 286

Mantra mini tree

CE  IP65 IK08 24V


Stainless steel AISI 316L

Supplied with 5 mt cable

Fixing to the tree directly with alimentation cable + clip cable locking

Opal diffuser

Driver 24V not included





Mantra fix





LED 7W / 700lm / 24V / H 700 mm

MAF1H1 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 1000 mm

MAF1H2 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 1500 mm

MAF1H3 ■ ■ ■

LED 7W / 700lm / 220/240V / H 700 mm

MAF2H1 ■ ■ ■ ■

LED 7W / 700lm / 220/240V / H 1000 mm

MAF2H2 ■ ■ ■ ■

LED 7W / 700lm / 220/240V / H 1500 mm

MAF2H3 ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech

NB Naturalblack

Drivers 24V p. 286

Mantra fix


CE **LED** IP65 IK08 24V / 220-240V

Stainless steel AISI 316L

Indirect light

Fixing to the ground with housing in stainless steel

Opal polycarbonate diffuser





LED 7W / 700lm / 220-240V / H 600 mm

MAC1H1 ■ ■ ■ ■

LED 7W / 700lm / 220-240V / H 800 mm

MAC1H2 ■ ■ ■ ■

LED 7W / 700lm / 220-240V / H 1000 mm

MAC1H3 ■ ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech

NB Naturalblack

Mantra ceiling


CE LED IP65 IK08 220-240V

Stainless steel AISI 316L

Indirect light

Fixing to the ceiling

Opal polycarbonate diffuser





7W / 700lm / 24V / H 800 mm

MAW1H3    

7W / 700lm / 220-240V / H 800 mm

MAW2H3    

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Drivers 24V p. 286

Mantra wall


  IP65 IK08 24V / 220-240V

Stainless steel AISI 316L

Indirect light

Wall installation

Opal polycarbonate diffuser





LED 7W / 700lm / 24V / H 500 mm

MAW1H1 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 750 mm

MAW1H2 ■ ■ ■ ■

LED 7W / 700lm / 220/240V / H 500 mm

MAW2H1 ■ ■ ■ ■

LED 7W / 700lm / 220/240V / H 750 mm

MAW2H2 ■ ■ ■

■ LED color Finishing

- | | |
|-----------------|--|
| 1 2200 K | IN Inox |
| 2 2700 K | BT Browntech |
| 3 3000 K | NB Naturalblack |

Drivers 24V p. 286

Mantra wall


CE LED IP65 IK08 24V / 220-240V

Stainless steel AISI 316L

Indirect light

Fixing to the wall

Opal polycarbonate diffuser





Mantra tree





LED 7W / 700lm / 24V / Fixing with bracket

MAT1H1 

LED 7W / 700lm / 24V / Fixing with alimentation cable and clip

MAT2H1

	LED color	Finishing
1	2200 K	IN 
2	2700 K	BT 
3	3000 K	NB 

Drivers 24V p. 286

Mantra tree

  IP65 IK08 24V

Stainless steel AISI 316L

Indirect light



Supplied with 5 mt cable

Fixing to the tree with bracket in stainless steel or directly with alimentation cable

+ clip cable locking

Opal polycarbonate diffuser

Driver 24V not included









LED 7W / 700lm / 24V / H 700 mm

SFLF1H1 

LED 7W / 700lm / 24V / H 1000 mm

SFLF1H2 

LED 7W / 700lm / 24V / H 1500 mm

SFLF1H3 

LED 7W / 700lm / 220/240V / H 700 mm

SFLF2H1 

LED 7W / 700lm / 220/240V / H 1000 mm

SFLF2H2 

LED 7W / 700lm / 220/240V / H 1500 mm

SFLF2H3 

LED color	Finishing
1 2200 K	IN  Inox
2 2700 K	BT  Browntech
3 3000 K	NB  Naturalblack

Drivers 24V p. 286

Spirit of Florence


  IP65 IK08 24V / 220-240V

Stainless steel AISI 316L

Indirect light

Fixing to the ground with housing in stainless steel

Opal polycarbonate diffuser









LED 7W / 700lm / 24V / H 700 mm

SPAF1H1 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 1000 mm

SPAF1H2 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 1500 mm

SPAF1H3 ■ ■ ■ ■

LED 7W / 700lm / 220/240V / H 700 mm

SPAF2H1 ■ ■ ■ ■

LED 7W / 700lm / 220/240V / H 1000 mm

SPAF2H2 ■ ■ ■ ■

LED 7W / 700lm / 220/240V / H 1500 mm

SPAF2H3 ■ ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech

NB Naturalblack

Drivers 24V p. 286

Spirit of Paris


CE LED IP65 IK08 24V / 220-240V

Stainless steel AISI 316L

Indirect light

Fixing to the ground with housing in stainless steel

Opal polycarbonate diffuser







Madama butterfly




LED 1,5W / 150lm / 24V / H 700 mm

MBTP1H1    

LED 1,5W / 150lm / 24V / H 1000 mm

MBTP1H2    


LED color	Finishing
1 2200 K	IN  Inox
2 2700 K	BT  Browntech
3 3000 K	NB  Naturalblack

Drivers 24V p. 286

Madama butterfly

  IP65 IK08 24V

Stainless steel AISI 316L
Fixing into the ground with spike
Supplied with cable L= 3 mt
Driver 24V not included





LED 4W / 400lm / 24V / H 1000 mm

FSTP1H1 ■ ■ ■ ■

LED 4W / 400lm / 24V / H 1400 mm

FSTP1H2 ■ ■ ■ ■

Accessories

ZA005 Housing

ZA006 Spike

LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Faust

CE LED IP65 IK08 24V


Stainless steel AISI 316L

Fixing into the ground with housing in stainless steel or spike

Opal diffuser

Supplied with 3 mt cable

Driver 24V not included





GU10 max 6W / 220/240V

AHP1H1



GU5,3 max 6W / 12V

AHP2H1



LED 4W / 400lm / 24V

AHP3H1



Optional

CASP2	IN	Visor Inox
CASP2	BT	Visor Browntech
CASP2	NB	Visor Naturalblack
SC1		Black honeycomb filter


LED color	LED lens	Finishing
2 2700 K	X 18°	IN Inox
3 3000 K	Y 25°	BT Browntech
	Z 38°	NB Naturalblack

Drivers 12 and 24V p. 286

Ad hoc

CE LED GU10 GU5,3 IP65 IK08 12V / 24V / 220-240V

- Stainless steel AISI 316L
- Suspension for trees, pergolas, etc.
- Transparent glass diffuser
- Supplied with 5 mt cable
- Fixing directly with alimentation cable and clip cable locking
- Connector IP68 included





E27 / 220-240V / IP 54

NAB1P1   

LED 4W / 400lm / 220-240V / IP 65

NAB1P2    

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Nabucco


CE  IP54/65 IK07 220-240V

Stainless steel AISI 316L

Fixing to the wall

Tranparent glass diffuser

Bulb not included





E27 / 220-240V / IP 54

NAB2P1 

LED 4W / 400lm / 220-240V / IP 65

NAB2P2 

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Nabucco


  IP54/65 IK07 220-240V

Stainless steel AISI 316L

Fixing to the wall

Striped glass diffuser

Bulb not included





LED 7W / 700lm / 24V / H 130 mm

TSC1H1    

LED 7W / 700lm / 24V / H 200 mm

TSC1H2    

LED 7W / 700lm / 220/240V / H 130 mm

TSC2H1    

LED 7W / 700lm / 220/240V / H 200 mm

TSC2H2    

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Drivers 24V p. 286

Tosca ceiling


  IP65 IK08 24V / 220-240V

Stainless steel AISI 316L

Fixing to the ceiling

Opal polycarbonate diffuser

The light diffuser is set back by 40mm (H 130) and 110mm (H 200)







Tosca wall



LED 7W / 700lm / 24V / H 130 mm

TSW1H1 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 200 mm

TSW1H2 ■ ■ ■ ■

LED 7W / 700lm / 220/240V / H 130 mm

TSW2H1 ■ ■ ■ ■

LED 7W / 700lm / 220/240V / H 200 mm

TSW2H2 ■ ■ ■ ■

LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Tosca wall

CE **LED** IP65 IK08 24V / 220-240V


Stainless steel AISI 316L

Fixing to the wall

Opal polycarbonate diffuser

360° adjustable beam direction

The light diffuser is set back by 40mm (H 130) and 110mm (H 200)





Chiodino





LED 1,5W / 150lm / 24V / H 700 mm

CH4P1H1 ■ ■ ■ ■ ■

LED 1,5W / 150lm / 24V / H 1000 mm

CH4P1H2 ■ ■ ■ ■ ■

LED color	Head shape	Finishing
1 2200 K	P Flat	IN Inox
2 2700 K	B Convexe	BT Browntech
3 3000 K		NB Naturalblack

Drivers 24V p. 286

Chiodino 4 P

CE LED IP65 IK08 24V


Stainless steel AISI 316L

Spike to be buried

Flat or convexe head

Equipped with 3 mt cable

Driver 24V not included









LED 4W / 400lm / 24V / H 700 mm

CH7P1H1 ■ ■ ■ ■ ■

LED 4W / 400lm / 24V / H 1000 mm

CH7P1H2 ■ ■ ■ ■ ■

LED color	Head shape	Finishing
1 2200 K	P Flat	IN Inox
2 2700 K	B Convexe	BT Browntech
3 3000 K		NB Naturalblack

Drivers 24V p. 286

Chiodino 7 P

CE LED IP65 IK08 24V


Stainless steel AISI 316L

Spike to be buried

Flat or convexe head

Equipped with 3 mt cable

Driver 24V not included





LED 4W / 400lm / 24V / H 500-900 mm above ground

CH7PTH1 ■ ■ ■ ■ ■


LED color	Head shape	Finishing
1 2200 K	P Flat	IN Inox
2 2700 K	B Convexe	BT Browntech
3 3000 K		NB Naturalblack

Drivers **24V** p. 286

Chiodino 7 telescopic

CE LED IP65 IK08 24V

Stainless steel AISI 316L
Adjustable height from 500 till 900 mm above ground
Spike to be buried
Flat or convexe head
Supplied with 3 mt cable
Driver 24V not included





LED 7W / 700lm / 24V / H 700 mm

CH13P1H1 ■ ■ ■ ■ ■

LED 7W / 700lm / 24V / H 1000 mm

CH13P1H2 ■ ■ ■ ■ ■

LED 7W / 700lm / 24V / H 1500 mm

CH13P1H3 ■ ■ ■ ■


LED color	Head shape	Finishing
1 2200 K	P Flat	IN Inox
2 2700 K	B Convexe	BT Browntech
3 3000 K		NB Naturalblack

Drivers 24V p. 286

Chiodino 13 P

CE LED IP65 IK08 24V

- Stainless steel AISI 316L
- Spike to be buried
- Flat or convexe head
- Supplied with 3 mt cable
- Opal polycarbonate diffuser





LED 7W / 700lm / 24V / H 350 mm

CH13FS1H1



LED 7W / 700lm / 24V / H 600 mm

CH13FS1H2



LED color

1 2200 K

2 2700 K

3 3000 K

Head shape

P Flat

B Convexe

Finishing

IN Inox

BT Browntech

NB Naturalblack

Drivers 24V p. 286

Chiodino 13 fix slim

CE LED IP65 IK08 24V


Stainless steel AISI 316L

Fixing with housing

Flat or convexe head

Connector IP68

Opal polycarbonate diffuser





LED 7W / 700lm / 24V / H 300 mm

CH13F1H2 ■ ■ ■ ■ ■

LED 7W / 700lm / 24V / H 400 mm

CH13F1H3 ■ ■ ■ ■ ■

LED 7W / 700lm / 220-240V / H 300 mm

CH13F2H2 ■ ■ ■ ■ ■

LED 7W / 700lm / 220-240V / H 400 mm

CH13F2H3 ■ ■ ■ ■ ■

LED color	Head shape	Finishing
1 2200 K	P Flat	IN Inox
2 2700 K	B Convexe	BT Browntech
3 3000 K		NB Naturalblack

Drivers 24V p. 286

Chiodino 13 fix


CE LED IP65 IK08 24V / 220-240V

Stainless steel AISI 316L

Fixing to the ground

Flat or convexe head

Opal polycarbonate diffuser









LED 7W / 700lm / 24V / H 80 mm

CH13W21H1 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 130 mm

CH13W21H2 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 180 mm

CH13W21H3 ■ ■ ■ ■

LED 7W / 700lm / 24V / H 230 mm

CH13W21H4 ■ ■ ■ ■

LED 7W / 700lm / 220-240V / H 130 mm

CH13W22H3 ■ ■ ■ ■

LED 7W / 700lm / 220-240V / H 180 mm

CH13W22H4 ■ ■ ■ ■

LED color	Head shape	Finishing
1 2200 K	P Flat	IN Inox
2 2700 K	B Convexe	BT Browntech
3 3000 K		NB Naturalblack

Drivers 24V p. 286

Chiodino 13 wall


CE LED IP65 IK08 24V / 220-240V

Stainless steel AISI 316L

Fixing to the wall

Flat or convexe head

Opal polycarbonate diffuser





Alter ego





LED 1W / 100lm / 24V / H 200 mm

AEG1P1H1 ■ ■ ■ ■

LED 1W / 100lm / 24V / H 600 mm

AEG1P1H2 ■ ■ ■ ■


LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Alter ego

CE **LED** IP65 IK08 24V

Stainless steel AISI 316L
Fixing into the ground with spike
Opal diffuser
Supplied with cable L= 3 mt
Driver 24V not included





Acorus





LED 4,8W / 450lm / 24V / H 500 mm

ACVP1H1   

LED 9,6W / 900lm / 24V / H 1000 mm

ACVP1H2   

LED 14,4W / 1350lm / 24V / H 1500 mm

ACVP1H3   

LED 19,2W / 1800lm / 24V / H 2000 mm

ACVP1H4   

LED color	Finishing
2 2700 K	IN 
3 3000 K	BT 

Drivers 24V p. 286

Acorus vertical


CE  IP65 IK08 24V

Stainless steel AISI 316L

Spike to be buried

Supplied with 5 mt cable

Driver 24V not included





LED 4,8W / 450lm / 24V / H 500 mm spike to be buried

ACHPP1H1 ■ ■ ■

LED 9,6W / 900lm / 24V / H 1000 mm spike to be buried

ACHPP1H2 ■ ■ ■

LED 14,4W / 1350lm / 24V / H 1500 mm spike to be buried

ACHPP1H3 ■ ■ ■

LED 19,2W / 1800lm / 24V / H 2000 mm spike to be buried

ACHPP1H4 ■ ■ ■

LED 4,8W / 450lm / 24V / H 500 mm fixing to the ground and to the wall

ACHFP1H1 ■ ■ ■

LED 9,6W / 900lm / 24V / H 1000 mm fixing to the ground and to the wall

ACHFP1H2 ■ ■ ■

LED 14,4W / 1350lm / 24V / H 1500 mm fixing to the ground and to the wall

ACHFP1H3 ■ ■ ■

LED 19,2W / 1800lm / 24V / H 2000 mm fixing to the ground and to the wall

ACHFP1H4 ■ ■ ■


LED color	Finishing
2 2700 K	IN Inox
3 3000 K	BT Browntech

Drivers 24V p. 286

Acorus horizontal

CE LED IP65 IK08 24V

Stainless steel AISI 316L
Spike to be buried, fixing to the ground and to the wall
Supplied with 5 mt cable
Driver 24V not included





LED 6W / 600lm / 24V / H 500 mm

ACWP1H1    


 LED color	Finishing
2 2700 K	IN  Inox
3 3000 K	BT  Browntech
	NB  Naturalblack

Drivers 24V p. 286

Acorus wall

CE  IP65 IK08 24V

Stainless steel AISI 316L
Fixing to the wall
Opal diffuser
Driver 24V not included









LED 4W / 400lm / 220/240V / 230 x H 700 mm

CAFR1D1    

LED 4W / 400lm / 220/240V / 230 x H 500 mm

CAFR1D2    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Carmen R1 fix


  IP65 IK08 220-240V

Stainless steel AISI 316L

Fixing to the ground with plate

On request cement mounting kit

24V version on request





LED 4W / 400lm / 220/240V / 230 x H 700 mm

CAFR2D1    

LED 4W / 400lm / 220/240V / 230 x H 500 mm

CAFR2D2    

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox


BT  Browntech

NB  Naturalblack

Carmen R2 fix

CE  IP65 IK08 220-240V

Stainless steel AISI 316L
Fixing to the ground with plate
On request cement mounting kit
24V version on request





Carmen R1 mobile sound / mobile

CE LED IP65 IK08 220-240V

Stainless steel AISI 316L

Supplied with 5 mt cable

10W bluetooth stereo sound system

MOBILE SOUND with 10W bluetooth stereo sound system

LED 4W / 400lm / 220/240V / 230 x H 700 mm

CASR1D1 ■ ■ ■ ■

LED 4W / 400lm / 220/240V / 230 x H 500 mm

CASR1D2 ■ ■ ■ ■

MOBILE

LED 4W / 400lm / 220/240V / 230 x H 700 mm

CAMR1D1 ■ ■ ■ ■

LED 4W / 400lm / 220/240V / 230 x H 500 mm

CAMR1D2 ■ ■ ■ ■

■ LED color

1 2200 K

2 2700 K


3 3000 K

Finishing

IN Inox

BT Browntech

NB Naturalblack





MOBILE SOUND with 10W bluetooth stereo sound system

LED 4W / 400lm / 220/240V / 230 x H 700 mm

CASR2D1 

LED 4W / 400lm / 220/240V / 230 x H 500 mm

CASR2D2 

MOBILE

LED 4W / 400lm / 220/240V / 230 x H 700 mm

CAMR2D1 

LED 4W / 400lm / 220/240V / 230 x H 500 mm

CAMR2D2 

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Carmen R2 mobile sound / mobile

CE  IP65 IK08 220-240V

Stainless steel AISI 316L

Supplied with 5 mt cable

10W bluetooth stereo sound system





LED 4W / 400lm / 230 x H 700 mm

CARR1D1    

LED 4W / 400lm / 230 x H 500 mm

CARR1D2    


 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech


NB  Naturalblack

Carmen R1 mobile rechargeable

  IP65 IK08

Stainless steel AISI 316L

Rechargeable with 7 hours autonomy





LED 4W / 400lm / 230 x H 700 mm

CARR2D1    

LED 4W / 400lm / 230 x H 500 mm

CARR2D2    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech


NB  Naturalblack

Carmen R2 mobile rechargeable

CE  IP65 IK08

Stainless steel AISI 316L

Rechargeable with 7 hours autonomy









LED 4W / 400lm / 220/240V / 450 x H 800 mm

MEFM1D1    

LED 4W / 400lm / 220/240V / 380 x H 500 mm

MEFM1D2    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Medea M1 fix


  IP65 IK08 220-240V

Stainless steel AISI 316L

Fixing to the ground with plate

On request cement mounting kit

24V version on request





LED 4W / 400lm / 220/240V / 600 x H 800 mm

MEFM2D1    

LED 4W / 400lm / 220/240V / 500 x H 500 mm

MEFM2D2    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Medea M2 fix


  IP65 IK08 220-240V

Stainless steel AISI 316L

Fixing to the ground with plate

On request cement mounting kit

24V version on request





MOBILE SOUND with 10W bluetooth stereo sound system

LED 4W / 400lm / 220/240V / 450 x H 800 mm

MESM1D1 ■ ■ ■ ■

LED 4W / 400lm / 220/240V / 380 x H 500 mm

MESM1D2 ■ ■ ■ ■

MOBILE

LED 4W / 400lm / 220/240V / 450 x H 800 mm

MEMM1D1 ■ ■ ■ ■

LED 4W / 400lm / 220/240V / 380 x H 500 mm

MEMM1D2 ■ ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech

NB Naturalblack


Medea M1 mobile sound / mobile

CE LED IP65 IK08 220-240V

Stainless steel AISI 316L

Supplied with 5 mt cable

10W bluetooth stereo sound system





MOBILE SOUND with 10W bluetooth stereo sound system

LED 4W / 400lm / 220/240V / 600 x H 800 mm

MESM2D1 ■ ■ ■ ■

LED 4W / 400lm / 220/240V / 500 x H 500 mm

MESM2D2 ■ ■ ■ ■

MOBILE

LED 4W / 400lm / 220/240V / 600 x H 800 mm

MEMM2D1 ■ ■ ■ ■

LED 4W / 400lm / 220/240V / 500 x H 500 mm

MEMM2D2 ■ ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox

BT Browntech

NB Naturalblack


Medea M2 mobile sound / mobile

CE LED IP65 IK08 220-240V

Stainless steel AISI 316L

Supplied with 5 mt cable

10W bluetooth stereo sound system





LED 4W / 400lm / 450 x H 800 mm

MERM1D1 ■ ■ ■ ■

LED 4W / 400lm / 380 x H 500 mm

MERM1D2 ■ ■ ■ ■

■ LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox


BT Browntech


NB Naturalblack

Medea M1 mobile rechargeable

CE LED IP65 IK08

Stainless steel AISI 316L
Rechargeable with 7 hours autonomy





LED 4W / 400lm / 600 x H 800 mm

MERM2D1    

LED 4W / 400lm / 500 x H 500 mm

MERM2D2    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox


BT  Browntech

NB  Naturalblack

Medea M2 mobile rechargeable

  IP65 IK08

Stainless steel AISI 316L
Rechargeable with 7 hours autonomy









LED 7W / 700lm / 220/240V / 250 x 250 x H 800 mm

CDFD1    

LED 7W / 700lm / 220/240V / 250 x 250 x H 500 mm

CDFD2    

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Casta diva fix

  IP65 IK08 220-240V

Stainless steel AISI 316L

Possibility to realize without handle

Fixing to the ground with plate





LED 7W / 700lm / 220/240V / 250 x 250 x H 800 mm

CDFR1D1    

LED 7W / 700lm / 220/240V / 250 x 250 x H 500 mm

CDFR1D2    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Casta diva fix R1

  IP65 IK08 220-240V

Stainless steel AISI 316L


Possibility to realize without handle

Fixing to the ground with plate





Casta diva fix rope





LED 7W / 700lm / 220/240V / 250 x 250 x H 800 mm

CDFP1D1    

LED 7W / 700lm / 220/240V / 250 x 250 x H 500 mm

CDFP1D2    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Casta diva fix rope


  IP65 IK08 220-240V

Stainless steel AISI 316L

Natural jute rope finishing

Possibility to realize without handle

Fixing to the ground with plate





LED 7W / 700lm / 220/240V / 250 x 250 x H 800 mm

CMDM1    

LED 7W / 700lm / 220/240V / 250 x 250 x H 500 mm

CMDM2    

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech


NB  Naturalblack

Casta diva mobile

  IP65 IK08 220-240V

Stainless steel AISI 316L

Supplied with 5 mt cable





LED 7W / 700lm / 220/240V / 250 x 250 x H 800 mm

CDMR1D1    

LED 7W / 700lm / 220/240V / 250 x 250 x H 500 mm

CDMR1D2    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox


BT  Browntech

NB  Naturalblack

Casta diva mobile R1

  IP65 IK08 220-240V

Stainless steel AISI 316L
Supplied with 5 mt cable





LED 7W / 700lm / 220/240V / 250 x 250 x H 800 mm

CDMP1D1    

LED 7W / 700lm / 220/240V / 250 x 250 x H 500 mm

CDMP1D2    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Casta diva mobile rope

  IP65 IK08 220-240V

Stainless steel AISI 316L

Natural jute rope finishing

Supplied with 5 mt cable





LED 5W / 500lm / 250 x 250 x H 800 mm

CDMRD1 ■ ■ ■ ■

LED 5W / 500lm / 250 x 250 x H 500 mm

CDMRD2 ■ ■ ■ ■


LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Casta diva mobile rechargeable

CE LED IP65 IK08

Stainless steel AISI 316L
Rechargeable with 7 hours autonomy





LED 5W / 500lm / 250 x 250 x H 800 mm

CDMRR1D1    

LED 5W / 500lm / 250 x 250 x H 500 mm

CDMRR1D2    

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Drivers 24V p. 286

Casta diva mobile R1 rechargeable

CE  IP65 IK08

Stainless steel AISI 316L

Rechargeable with 7 hours autonomy





LED 5W / 500lm / 250 x 250 x H 800 mm

CDMRP1D1    

LED 5W / 500lm / 250 x 250 x H 500 mm

CDMRP1D2    

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Casta diva mobile rope rechargeable

  IP65 IK08

Stainless steel AISI 316L

Natural jute rope finishing

Rechargeable with 7 hours autonomy









LED 6W / 600lm / 220/240V / 150 x 150 x H 300 mm

CDD1

LED 6W / 600lm / 220/240V / 200 x 200 x H 400 mm

CDD2

LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN Inox


BT Browntech

NB Naturalblack

Casta diva wall

CE LED IP65 IK08 220-240V

Stainless steel AISI 316L
Fixing to the wall





E27 / 220-240V / 220 x 140 x H 400 mm

CDDR1H1 

LED 4W / 400lm / 220-240V / 220 x 140 x H 400 mm

CDDR2H1 

E27 / 220-240V / 165 x 112 x H 320 mm

CDDR1H2 

LED 4W / 400lm / 220-240V / 165 x 112 x H 320 mm

CDDR2H2 


E27 / 220-240V / 165 x 112 x H 400 mm

CDDR1H3 

LED 4W / 400lm / 220-240V / 165 x 112 x H 400 mm

CDDR2H3 


-  LED color
- 1** 2200 K
- 2** 2700 K
- 3** 3000 K

- Finishing
- IN**  Inox
- BT**  Browntech
- NB**  Naturalblack

Casta diva wall R1

  IP65 IK08 220-240V

Stainless steel AISI 316L
Fixing to the wall
Opal polycarbonate diffuser





E27 / 220-240V / 100 x 112 x H 320 mm

CDDR1H4 

LED 4W / 400lm / 220-240V / 100 x 112 x H 320 mm

CDDR2H4 

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Casta diva wall R1

  IP65 IK08 220-240V

Stainless steel AISI 316L

Fixing to the wall

Opal diffuser





Casta diva wall V1





E27 / 220-240V / 220 x 140 x H 400 mm

CDDV1H1 

LED 4W / 400lm / 220-240V / 220 x 140 x H 400 mm

CDDV2H1 

E27 / 220-240V / 165 x 112 x H 320 mm

CDDV1H2 

LED 4W / 400lm / 220-240V / 165 x 112 x H 320 mm

CDDV2H2 

E27 / 220-240V / 165 x 112 x H 400 mm

CDDV1H3 

LED 4W / 400lm / 220-240V / 165 x 112 x H 400 mm

CDDV2H3 

E27 / 220-240V / 100 x 112 x H 320 mm

CDDV1H4 

LED 4W / 400lm / 220-240V / 100 x 112 x H 320 mm

CDDV2H4 

Casta diva wall V1


CE LED E27 IP65 IK08 220-240V


Stainless steel AISI 316L

Fixing to the wall

Transparent, smoked or amber glass diffuser

Integrated LED or E27

LED color	Glasses color	Finishing
1 2200 K	T Transparent	IN  Inox
2 2700 K	A Amber	BT  Browntech
3 3000 K	F Smoked	NB  Naturalblack





E27 / 220-240V / 220 x 140 x H 400 mm

CDDV1H1M 

LED 4W / 400lm / 220-240V / 220 x 140 x H 400 mm

CDDV2H1M 

E27 / 220-240V / 165 x 112 x H 320 mm

CDDV1H2M 

LED 4W / 400lm / 220-240V / 165 x 112 x H 320 mm

CDDV2H2M 

E27 / 220-240V / 165 x 112 x H 400 mm

CDDV1H3M 

LED 4W / 400lm / 220-240V / 165 x 112 x H 400 mm

CDDV2H3M 

E27 / 220-240V / 100 x 112 x H 400 mm

CDDV1H4M 

LED 4W / 400lm / 220-240V / 100 x 112 x H 400 mm

CDDV2H4M 

Casta diva wall V1

CE LED E27 IP65 IK08 220-240V

Stainless steel AISI 316L

Fixing to the wall

Thousand lines opal glass diffuser

Integrated LED or E27

 LED color

1 2200 K

2 2700 K


3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack





LED 14W / 1400lm / 24V / Up & down

BL13AP1H1 

LED 14W / 1400lm / 220-240V / Up & down

BL13AP2H1 


LED color	Finishing
1 2200 K	IN 
2 2700 K	BT 
3 3000 K	NB 

Drivers 24V p. 286

Baloss 13

  IP65 IK08 24V / 220-240V

Stainless steel AISI 316L
Fixing to the wall
Backward opal diffuser









LED 3,6W / 360lm / 220-240V / H 160 mm



CHF1    

LED 3,6W / 360lm / 220-240V / H 300 mm

CHF2    

Accessories

ZA003 Cement mounting kit

LED color	Finishing
1 2200 K	IN 
2 2700 K	BT 
3 3000 K	NB 

Chaparral


CE  IP65 IK08 220-240V


Stainless steel AISI 316L

Fixing to the ground

Indirect light downwards

Transparent glass diffuser





Ad lunam



LED 3W / 300lm / 220-240V

ALF2H1    

 LED color

1 2200 K


2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Ad lunam

CE  IP65 IK08 220-240V

Stainless steel AISI 316L

Fixing to the wall

Indirect light





Nessun dorma





LED 3W / 300lm / 24V / H 200 mm

NDT1H1    

LED 3W / 300lm / 24V / H 350 mm

NDT1H2    

LED 3W / 300lm / 24V / H 600 mm

NDT1H3    

LED 3W / 300lm / 220-240V / H 350 mm

NDT2H2    

LED 3W / 300lm / 220-240V / H 600 mm

NDT2H3    

Accessories

ZA004 Cement mounting kit

ZA005 Housing

LED color		Finishing	
1	2200 K	IN	Inox
2	2700 K	BT	Browntech
3	3000 K	NB	Naturalblack

Drivers 24V p. 286

Nessun dorma

CE  IP65 IK08 24V / 220-240V


Stainless steel AISI 316L

Indirect light

Fixing to the ground

On request cement mounting kit

On request housing









LED 3W / 300lm / 24V

NDW10    


LED color	Finishing
1 2200 K	IN 
2 2700 K	BT 
3 3000 K	NB 

Drivers 24V p. 286

Nessun dorma wall 10

  IP65 IK08 24V

Stainless steel AISI 316L
Fixing to the wall
Indirect light
Driver 24V not included





LED 3W / 300lm / 24V
NDW1017T1    

LED 3W / 300lm / 220-240V
NDW1017T2    


LED color	Finishing
1 2200 K	IN 
2 2700 K	BT 
3 3000 K	NB 

Drivers 24V p. 286

Nessun dorma wall 10-17

CE  IP65 IK08 24V / 220-240V

Stainless steel AISI 316L
Fixing to the wall
Indirect light





LED 3W / 450lm / 220-240V

NDW183    

LED 4,4W / 650lm / 220-240V

NDW184    

 LED color


2 2700 K

3 3000 K

Finishing

IN 

BT 

NB 


Nessun dorma wall 18

CE  IP65 IK08 220-240V

Stainless steel AISI 316L

Fixing to the wall

Indirect light









LED 3W / 300lm / 24V / H 350 mm

MIP3H1    

LED 3W / 300lm / 24V / H 600 mm

MIP3H2    

LED 3W / 300lm / 24V / H 800 mm

MIP3H3    

LED 3W / 300lm / 24V / H 1200 mm

MIP3H4    

Accessories

ZA005 Housing

ZA007 Spike

LED color	Finishing
1 2200 K	IN 
2 2700 K	BT 
3 3000 K	NB 

Drivers 24V p. 286

Mimi


  IP65 IK08 24V

Stainless steel AISI 316L

Fixing to the ground with spike or housing

Indirect light

Supplied with 3 mt cable with connector IP68





LED 1W / 100lm / 24V / H 550 mm (350 above ground)

MIS1H1    

LED 1W / 100lm / 24V / H 850 mm (650 above ground)

MIS1H2    

LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Mimì mini


CE  IP65 IK08 24V

Stainless steel AISI 316L

Fixing to the ground with spike

Indirect light

Supplied with 3 mt cable with connector IP68





LED 4W / 450lm / 24V / H 1800 mm

BBX1P1H1   

LED 4W / 450lm / 24V / H 2200 mm

BBX1P1H2   

LED 4W / 450lm / 24V / H 2600 mm

BBX1P1H3   

LED 4W / 450lm / 24V / H 3000 mm

BBX1P1H4   

LED 4W / 450lm / 220-240V / H 1800 mm

BBX1P2H1   

LED 4W / 450lm / 220-240V / H 2200 mm

BBX1P2H2   

LED 4W / 450lm / 220-240V / H 2600 mm

BBX1P2H3   

LED 4W / 450lm / 220-240V / H 3000 mm

BBX1P2H4   

Accessories

BB1CA1 Housing for 1 bamboo

BB1CA2 Housing for 2 bamboo

BB1CA3 Housing for 3 bamboo

 LED color

1 2200 K

2 2700 K

3 3000 K

Finishing

IN  Inox

BT  Browntech

Drivers 24V p. 286

Bamboo

  IP65 IK08 24V / 220-240V


Stainless steel AISI 316L

Opal glass diffuser

Fixing to the ground with housing in stainless steel

Supplied with 3 mt cable

24V version power supply excluded







Backspin plus



GU10 / 220-240V

BAP1T1 

LED 3.6W / 360lm / 24V

BAP2T1 

LED 5W / 550lm / 24V

BAP3T1 

GU5,3 / 12V

BAP7T1 

Fixing accessories

- BAPPB1**  Low spike
- BAPPA1**  Spike with telescopic rod
H 300-700 mm above ground
- BAPFM1**  Adjustable wall fixing plate 360°
- BAPFA1**  Fixing plate for tree with belts L=2.0 mt

Optional

CASP1  Visor


 LED color	 LED lens	Finishing
2 2700 K	X 18°	IN 
3 3000 K	Y 25°	BT 
	Z 38°	NB 

Drivers 12V and 24V p. 286

Backspin plus

   IP65 IK08 12V / 24V / 220-240V

Stainless steel AISI 316L
Projector with fixing accessories
Transparent glass diffuser
Supplied with black honeycomb filter
Supplied with 3 mt cable





GU10 max 3x5W / 220-240V / Spike

BAXL    

GU5,3 max 3x5W / 12V / Spike

BAXL2    

GU10 max 3x5W / 220-240V / Fixing for trees

BAXT    

GU5,3 max 3x5W / 12V / Fixing for trees

BAXT2    

On request

CASXL    Visor

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack

Backspin XL

CE  IP65 IK08 220-240V / 12V

Stainless steel AISI 316L


Spike to be buried and fixing system for trees

Fixing to trees with n. 2 belts L= 2 mt


Bulb not included

Supplied with 3 mt cable

On request visor (rif. + CASXL)



Spike



Fixing for trees

On request visor







RASCASSE 8

LED 2W / 200lm / 24V / 84x84 mm

RAW08F1 ■ ■ ■ ■

RAW08CA Housing

RASCASSE 13

LED 3,6W / 360lm / 220-240V

RAW13F2 ■ ■ ■ ■

LED 5W / 500lm / 220-240V

RAW13F4 ■ ■ ■ ■

RAW13CA Housing

RAW13CB Fixing kit for wood th. 2 cm

RASCASSE 25

4W / 690lm / 220-240V

RAW25F2 ■ ■ ■ ■

LED 8W / 1380lm / 220-240V

RAW25F4 ■ ■ ■ ■




RAW25CA Housing

LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Rascasse

CE LED IP65 IK08 24V / 220-240V 500mA

Stainless steel AISI 316L
Fixing with housing in stainless steel
Indirect light
Transparent glass diffuser
Supplied with 30 cm cable





RASCASSE 8

LED 2W / 200lm / 24V / 84x84 mm

RAD08F1



RAW08CA Housing

RASCASSE 13

LED 3,6W / 360lm / 220-240V

RAD13F2



LED 5W / 500lm / 220-240V

RAD13F4



RAW13CA Housing

RAD13CB Fixing kit for wood th. 2 cm



LED color	LED Optics	Finishing
1 2200 K	X 10°	IN Inox
2 2700 K	Y 25°	BT Browntech
3 3000 K	Z 40°	NB Naturalblack



Rascasse direct

CE LED IP67 IK08 24V / 220-240V

Stainless steel AISI 316L
Fixing with housing in stainless steel
Direct light
Opal/transparent glass diffuser
Supplied with 30 cm cable





YUUKI 6 DOWN

GU10 max 7W LED / 220-240V

YU6MF1

LED 1,3W / 150lm / 220-240V

YU6MF2

YUUKI 6 UP & DOWN

2XGU10 max 7W LED / 220-240V

YU6BF1

2x LED 1,3W / 300lm / 220-240V

YU6BF2

LED color	LED Optics	Finishing
3 3000 K	X 10°	IN Inox
	Y 25°	BT Browntech
	Z 40°	NB Naturalblack

Yuuki 6


CE LED IP65 IK09 220-240V

Stainless steel AISI 316L

Fixing to the wall

Transparent glass diffuser

Supplied with 15 cm cable





LED 14W / 1400lm / 24V / Up & down

YU13AP1H1 ■ ■ ■ ■

LED 14W / 1400lm / 220-240V / Up & down

YU13AP2H1 ■ ■ ■ ■

LED 7W / 700lm / 24V / Down

YU13BP1H1 ■ ■ ■ ■

LED 7W / 700lm / 220-240V / Down

YU13BP2H1 ■ ■ ■ ■


LED color	Finishing
1 2200 K	IN Inox
2 2700 K	BT Browntech
3 3000 K	NB Naturalblack

Drivers 24V p. 286

Yuuki 13

CE **LED** IP65 IK08 24V / 220-240V

Stainless steel AISI 316L
Fixing to the wall
Backword 40 mm opal diffuser





E27 max 12W LED / 220-240V / Light 1 side / H 300mm

SA01H1   

E27 max 12W LED / 220-240V / Light 1 side / H 600mm

SA01H2   

E27 max 12W LED / 220-240V / Light 1 side / H 900mm

SA01H3   

E27 max 12W LED / 220-240V / Light 4 sides / H 300mm

SA04H1   

E27 max 12W LED / 220-240V / Light 4 sides / H 600mm

SA04H2   


E27 max 12W LED / 220-240V / Light 4 sides / H 900mm

SA04H3   

On request

ZA011 Cement mounting kit

Finishing

IN 


BT 

NB 

Sam

  IP65 IK08 220-240V

Stainless steel AISI 316L
Ground fixing with screws and plugs
Sand blasted glass diffuser









LED 1,2W / 100lm / 24V / transparent glass

MR06F1 ■ ■ ■ ■ ■

LED 1,2W / 100lm / 24V / opal glass

MR06F2 ■ ■ ■ ■ ■

LED color	LED Optics	Finishing
1 2200 K	X 10°	IN Inox
2 2700 K	Y 25°	BT Browntech
3 3000 K	Z 40°	NB Naturalblack

Marell 6

CE LED IP67 IK09 24V

Stainless steel AISI 316L


Fixing with housing

Indirect light

Sand blasted/transparent glass diffuser

Supplied with 30 cm cable

Driver 24V not included





GU10 max 1x7W LED / 220-240V / Round ring

MR13F21 ■ ■ ■

MR13CA1 Housing

GU10 max 1x7W LED / 220-240V / Round ring flush with floor

MR13F22 ■ ■ ■

MR13CA2 Housing

GU10 max 1x7W LED / 220-240V / Square ring

MR13F23 ■ ■ ■

MR13CA1 Housing

GU5.3 max 1x7W LED / 12V / Round ring

MR13F24 ■ ■ ■

MR13CA1 Housing

GU5.3 max 1x7W LED / 12V / Round ring flush with floor

MR13F25 ■ ■ ■

MR13CA2 Housing

GU5.3 max 1x7W LED / 12V / Square ring

MR13F26 ■ ■ ■

MR13CA1 Housing

Finishing

IN Inox

BT Browntech

NB Naturalblack

Marell 13

CE LED GU10 IP67 IK10 12V / 220-240V


Stainless steel AISI 316L

Fixing with housing

Direct light

Sand blasted/transparent glass diffuser

Supplied with 60 cm cable





E27 PAR30 max 12W / 220-240V / Round ring

MR22F31 

MR22CA1 Stainless steel housing

MR22AN1 Stainless steel ring nut for ground

LED 11W / 2000lm / 220-240V / Round ring

MR22P32 

MR22CA1 Stainless steel housing

MR22AN1 Stainless steel ring nut for ground

LED 16,5W / 2850lm / 220-240V / Round ring

MR22P33 

MR22CA1 Stainless steel housing

MR22AN1 Stainless steel ring nut for ground

LED 23,5W / 3940lm / 220-240V / Round ring

MR22P35 

MR22CA1 Stainless steel housing

MR22AN1 Stainless steel ring nut for ground

 LED color	 LED Optics	Finishing
1 2200 K	X 10°	IN 
2 2700 K	Y 25°	BT 
3 3000 K	Z 40°	NB 



Marell 22

CE LED GU10 IP67 IK10 220-240V

Stainless steel AISI 316L

Stainless steel housing


Direct light

Transparent glass diffuser (on request sand blasted)

Adjustable optics ± 20° and rotating on the axis 360°

Supplied with 30 cm cable welded to the connector IP68

With anti-condensation barrier





GX53 7W / 220-240V / H 145

FMF1

FMCA1 Housing

LED 4W / 300lm / 220-240V / H 200

FMF2

FMCA1 Housing

- LED color

3

3000 K

4

4000 K
- Finishing

IN

Inox

BT

Browntech

NB

Naturalblack

Follow me


CE

LED

GU10

 IP67 IK10 220-240V

Stainless steel AISI 316L
Fixing with housing
Sand blasted polycarbonate diffuser
Supplied with 30 cm cable
The top part can be customised





1 socket version / H 300 mm

MH1 

2 sockets version / H 500 mm

MH2 

Accessories

ZA001 Cement mounting kit

Finishing

IN  Inox

BT  Browntech

NB  Naturalblack


Mr Help

 IP65 IK08

Stainless steel AISI 316L

Fixing to the ground

Versions 1 socket and 2 sockets





1 socket / H 350 mm

EG1 

Finishing

IN  Inox

BT  Browntech


NB  Naturalblack

Energy Ghost

CE IP67 IK10

Stainless steel AISI 316L

Manual retractable



DRIVERS 24V

Code	Type	Input	Output	IP	Dimensions
AL65001	ON/OFF	220-240V 50-60Hz	24V / 12W	65	50x50x25
AL67D006	Dimm 1-10V / PWM / resistance	90-305V AC	24V / 16W	30	148x40x32
AL67001	ON/OFF	90-264V	24V / 20W	67	118x35x26
AL67D007	Dimm 1-10V / PWM / resistance	90-305V AC	24V /25W	67	148x40x32
AL67002	ON/OFF	90-264V	24V / 35W	67	148x40x30
AL67D003	Dimm 0-10V / PWM / resistance	90-305V	24V / 40W	67	150x53x35
AL67D004	Dimm 0-10V / PWM / resistance	90-305V	24V / 60W	67	150x53x35
AL67D008	DALI	100-305V AC	24V / 75W	67	180x63x35,5
AL67D005	Dimm 0-10V / PWM / resistance	90-305V	24V / 90W	67	171x63x38
AL67020	ON/OFF	220-240V	24V/14,4W	67	79x38x25
AL67021	ON/OFF	220-240V	24V/36W	67	120x38x25

DRIVERS 12V

Code	Type	Input	Output	IP	Dimensions
AL65012	ON/OFF	220-240V 50-60Hz	12V / 12W	65	50x50x25
AL67009	ON/OFF	90-305V AC	12V / 16W	67	148x40x32
AL67010	ON/OFF	90-305V AC	12V / 25W	67	148x40x32
AL67011	ON/OFF	90-305V AC	12V / 40W	67	150x53x35
AL67022	ON/OFF	220-240V	12V/14,4W	67	79x38x25
AL67023	ON/OFF	220-240V	12V/24W	67	120x38x25

CLEANING KIT

Code	Type
PUL100	Cleaning kit 100ml
PUL250	Cleaning kit 250ml



inverlight

via P. Stucchi, 2 \ 20872 Cornate d'Adda (MB) Italy

tel. +39 039 6060754

www.inverlight.it \ info@inverlight.it